

Verified Answers Researched by Industry Experts and almost 100% correct

70-561CSharp exam questions updated on regular basis

Same type as the certification exams, 70-561CSharp exam preparation is in multiple-choice questions (MCQs).

Tested by multiple times before publishing

Try free 70-561CSharp exam demo before you decide to buy it in Test-Inside.com.

Note: This pdf demo does not include the question's picture.

Exam : Microsoft 70-561Csharp

Title : TS: MS .NET Framework 3.5, ADO.NET Application Development

1. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

The application analyzes large amounts of transaction data that are stored in a different database.

You write the following code segment. (Line numbers are included for reference only.)

```
01 using (SqlConnection connection = new
SqlConnection(sourceConnectionString))
02 using (SqlConnection connection2 = new
SqlConnection(destinationConnectionString))
03 using (SqlCommand command = new SqlCommand())
04 {
05 connection.Open();
06 connection2.Open();
07 using (SqlDataReader reader = command.ExecuteReader())
08 {
09 using (SqlBulkCopy bulkCopy = new
SqlBulkCopy(connection2))
10 {
11
12 }
13 }
14 }
```

You need to copy the transaction data to the database of the application.

Which code segment should you insert at line 11?

A. `reader.Read()`

`bulkCopy.WriteToServer(reader);`

B. `bulkCopy.DestinationTableName = "Transactions";`

`bulkCopy.WriteToServer(reader);`

C. `bulkCopy.DestinationTableName = "Transactions";`

`bulkCopy.SqlRowsCopied += new`

`SqlRowsCopiedEventHandler(bulkCopy_SqlRowsCopied);`

D. `while (reader.Read())`

`{`

`bulkCopy.WriteToServer(reader);`

`}`

Answer: B

2. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET.

You need to ensure that the application can connect to any type of database.

What should you do?

A. Set the database driver name in the connection string of the application, and then create the connection object in the following manner.

```
DbConnection connection = new OdbcConnection(connectionString);
```

B. Set the database provider name in the connection string of the application, and then create the connection object in the following manner.

```
DbConnection connection = new OleDbConnection(connectionString);
```

C. Create the connection object in the following manner.

```
DbProviderFactory factory =
```

```
DbProviderFactories.GetFactory("System.Data.Odbc");
```

```
DbConnection connection = factory.CreateConnection();
```

D. Create the connection object in the following manner.

```
DbProviderFactory factory =
```

```
DbProviderFactories.GetFactory(databaseProviderName);
```

```
DbConnection connection = factory.CreateConnection();
```

Answer: D

3. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

You write the following code segment.

```
string queryString = "Select Name, Age from dbo.Table_1";
```

```
SqlCommand command = new SqlCommand(queryString,  
(SqlConnection)connection);
```

You need to get the value that is contained in the first column of the first row of the result set returned by the query.

Which code segment should you use?

A. `var value = command.ExecuteScalar();`

```
string requiredValue = value.ToString();
```

B. `var value = command.ExecuteNonQuery();`

```
string requiredValue = value.ToString();
```

C. `var value = command.ExecuteReader(CommandBehavior.SingleRow);`

```
string requiredValue = value[0].ToString();
```

D. `var value = command.ExecuteReader(CommandBehavior.SingleRow);`

```
string requiredValue = value[1].ToString();
```

Answer: A

4. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET.

The application contains a DataSet object named OrderDS that has the Order and OrderDetail tables as shown in the following exhibit.

You write the following code segment. (Line numbers are included for reference only.)

```
01 private void GetOrders(SqlDataConnection cn) {
```

```
02 SqlCommand cmd = cn.CreateCommand();
```

```
03 cmd.CommandText = "Select * from [Order];
```

```
Select * from [OrderDetail];";
```

```
04 SqlDataAdapter da = new SqlDataAdapter(cmd);
```

```
05
```

```
06 }
```

You need to ensure that the Order and the OrderDetail tables are populated.

Which code segment should you insert at line 05?

A. `da.Fill(OrderDS);`

B. `da.Fill(OrderDS.Order);`

```
da.Fill(OrderDS.OrderDetail);
```

C. `da.TableMappings.AddRange(new DataTableMapping[] {`

```
new DataTableMapping("Table", "Order"),
```

```
new DataTableMapping("Table1", "OrderDetail"));
```

```
da.Fill(OrderDS);
```

D. `DataTableMapping mapOrder = new DataTableMapping();`

```
mapOrder.DataSetTable = "Order";
DataTableMapping mapOrderDetail = new DataTableMapping();
mapOrder.DataSetTable = "OrderDetail";
da.TableMappings.AddRange(new DataTableMapping[]
{ mapOrder, mapOrderDetail });
Da.Fill(OrderDS);
Answer: C
```

5. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application contains a DataSet object named orderDS. The object contains a table named Order as shown in the following exhibit.

The application uses a SqlDataAdapter object named daOrder to populate the Order table.

You write the following code segment. (Line numbers are included for reference only.)

```
01 private void FillOrderTable(int pageIndex) {
02 int pageSize = 5;
03
04 }
```

You need to fill the Order table with the next set of 5 records for each increase in the pageIndex value.

Which code segment should you insert at line 03?

A. string sql = "SELECT SalesOrderID, CustomerID, OrderDate FROM Sales.SalesOrderHeader";

```
daOrder.SelectCommand.CommandText = sql;
daOrder.Fill(orderDS, pageIndex, pageSize, "Order");
```

B. int startRecord = (pageIndex - 1) * pageSize;

```
string sql = "SELECT SalesOrderID, CustomerID, OrderDate FROM Sales.SalesOrderHeader";
```

```
daOrder.SelectCommand.CommandText = sql;
daOrder.Fill(orderDS, startRecord, pageSize, "Order");
```

C. string sql = string.Format("SELECT TOP {0} SalesOrderID, customerID, orderDate FROM Sales.SalesOrderHeader WHERE SalesOrderID > {1}", pageSize, pageIndex);

```
daOrder.SelectCommand.CommandText = sql;
```

```
daOrder.Fill(orderDS, "Order");
```

D. int startRecord = (pageIndex - 1) * pageSize;

```
string sql = string.Format("SELECT TOP {0} SalesOrderID, CustomerID, orderDate FROM Sales.SalesOrderHeader WHERE SalesOrderID > {1}", pageSize, startRecord);
```

```
daOrder.SelectCommand.CommandText = sql;
```

```
daOrder.Fill(orderDS, "Order");
```

Answer: B

6. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET.

The application contains a SqlDataAdapter object named daOrder. The SelectCommand property of the daOrder object is set.

You write the following code segment. (Line numbers are included for reference only.)

```
01 private void ModifyDataAdapter() {
02
03 }
```

You need to ensure that the daOrder object can also handle updates.

Which code segment should you insert at line 02?

A. SqlCommandBuilder cb = new SqlCommandBuilder(daOrder);

```
cb.RefreshSchema();
```


8. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

You write the following code segment. (Line numbers are included for reference only.)

```
01 using (SqlConnection connection = new
SqlConnection(connectionString)) {
02 SqlCommand cmd = new SqlCommand(queryString, connection);
03 connection.Open();
04
05 while (sdrdr.Read()){
06 // use the data in the reader
07 }
08 }
```

You need to ensure that the memory is used efficiently when retrieving BLOBs from the database.

Which code segment should you insert at line 04?

- A. SqlDataReader sdrdr = cmd.ExecuteReader();
- B. SqlDataReader sdrdr = cmd.ExecuteReader(CommandBehavior.Default);
- C. SqlDataReader sdrdr = cmd.ExecuteReader(CommandBehavior.SchemaOnly);
- D. SqlDataReader sdrdr = cmd.ExecuteReader(CommandBehavior.SequentialAccess);

Answer: D

9. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

The application throws an exception when the SQL Connection object is used.

You need to handle the exception.

Which code segment should you use?

- A. try
{
if(null!=conn)
conn.Close();
// code for the query
}
catch (Exception ex)
{
// handle exception
}
finally
{
if(null==conn)
conn.Open();
}
B. try
{
conn.Close();
// code for the query
}
catch (Exception ex)
{
// handle exception
}

```

finally
{
if(null!=conn)
conn.Open();
}
C. try
{
conn.Open();
// code for the query
}
catch (Exception ex)
{
// handle exception
}
finally
{
if(null!=conn)
conn.Close();
}
D. try
{
conn.Open();
// code for the query
}
catch (Exception ex)
{
// handle exception
}
finally
{
if(null==conn)
conn.Close();
}

```

Answer: C

10. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET.

The application contains a TextBox control named txtProductID. The application will return a list of active products that have the ProductID field equal to the txtProductID.Text property.

You write the following code segment. (Line numbers are included for reference only.)

```

01 private DataSet GetProducts(SqlConnection cn) {
02 SqlCommand cmd = new SqlCommand();
03 cmd.Connection = cn;
04 SqlDataAdapter da = new SqlDataAdapter(cmd);
05 DataSet ds = new DataSet();
06
07 da.Fill(ds);
08 return ds;
09 }

```

You need to populate the DataSet object with product records while avoiding possible SQL injection attacks.

Which code segment should you insert at line 06?

- A. cmd.CommandText = string.Format("sp_sqlexec 'SELECT ProductID, Name FROM Product WHERE ProductID={0} AND IsActive=1'", txtProductID.Text);
- B. cmd.CommandText = string.Format("SELECT ProductID, Name FROM

```

Product WHERE ProductID={0} AND IsActive=1", txtProductID.Text);
cmd.Prepare();
C. cmd.CommandText = string.Format("SELECT ProductID, Name FROM
Product WHERE ProductID={0} AND IsActive=1", txtProductID.Text);
cmd.CommandType = CommandType.TableDirect;
D. cmd.CommandText = "SELECT ProductID, Name FROM Product WHERE
ProductID=@productID AND IsActive=1";
cmd.Parameters.AddWithValue("@productID", txtProductID.Text);
Answer: D

```

11. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application has a DataTable object named OrderDetailTable. The object has the following columns:

```

.ID
.OrderID
.ProductID
.Quantity
.LineTotal

```

The OrderDetailTable object is populated with data provided by a business partner. Some of the records contain a null value in the LineTotal field and 0 in the Quantity field.

You write the following code segment. (Line numbers are included for reference only.)

```

01 DataColumn col = new DataColumn("UnitPrice", typeof(decimal));
02
03 OrderDetailTable.Columns.Add(col);

```

You need to add a DataColumn named UnitPrice to the OrderDetailTable object.

Which line of code should you insert at line 02?

- A. col.Expression = "LineTotal/Quantity";
- B. col.Expression = "LineTotal/ISNULL(Quantity, 1)";
- C. col.Expression = "LineTotal.Value/ISNULL(Quantity.Value,1)";
- D. col.Expression = "iif(Quantity > 0, LineTotal/Quantity, 0)";

Answer: D

12. You create an application by using the Microsoft .NET Framework 5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

You need to separate the security-related exceptions from the other exceptions for database operations at run time.

Which code segment should you use?

- A.

```
catch (System.Security.SecurityException ex)
{
//Handle all database security related exceptions.
}
```
- B.

```
catch (System.Data.SqlClient.SqlException ex)
{
for (int i = 0; i < ex.Errors.Count; i++){
if (ex.Errors[i].Class.ToString() == "14") {
//Handle all database security related exceptions.
}
}
else{
//Handle other exceptions
}
}
}
```
- C.

```
catch (System.Data.SqlClient.SqlException ex)
{
for (int i = 0; i < ex.Errors.Count; i++){
```

```

if (ex.Errors[i].Number == 14){
//Handle all database security related exceptions.
}
else{
//Handle other exceptions
}
}
}
D. catch (System.Data.SqlClient.SqlException ex)
{
for (int i = 0; i < ex.Errors.Count; i++){
if (ex.Errors[i].Message.Contains("Security")){
//Handle all database security related exceptions.
}
else{
//Handle other exceptions
}
}
}
}

```

Answer: B

13. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

The connection string of the application is defined in the following manner.

```
"Server=Prod;Database=WingtipToys;Integrated
Security=SSPI;Asynchronous Processing=true"
```

The application contains the following code segment. (Line numbers are included for reference only.)

```

01 protected void UpdateData(SqlCommand cmd) {
02 cmd.Connection.Open();
03
04 lblResult.Text = "Updating ...";
05 }

```

The cmd object takes a long time to execute.

You need to ensure that the application continues to execute while cmd is executing.

What should you do?

A. Insert the following code segment at line 03.

```
cmd.BeginExecuteNonQuery(new AsyncCallback(UpdateComplete), cmd);
```

Add the following code segment.

```

private void UpdateComplete (IAsyncResult ar) {
int count = (int)ar.AsyncState;
LogResults(count);
}

```

B. Insert the following code segment at line 03.

```
cmd.BeginExecuteNonQuery(new AsyncCallback(UpdateComplete), cmd);
```

Add the following code segment.

```

private void UpdateComplete (IAsyncResult ar) {
SqlCommand cmd = (SqlCommand)ar.AsyncState;
int count = cmd.ExecuteNonQuery(ar);
LogResults(count);
}

```

C. Insert the following code segment at line 03.

```

cmd.StatementCompleted += new
StatementCompletedEventHandler(UpdateComplete);

```



```

}
RecordCount = myReader.RecordsAffected;
C. while (myReader.HasRows)
{
while (myReader.Read())
{
//Write logic to process data for the second result.
RecordCount = RecordCount + 1;
myReader.NextResult();
}
}

```

```

D. while (myReader.HasRows)
{
while (myReader.Read())
{
//Write logic to process data for the second result.
RecordCount = RecordCount + 1;
}
myReader.NextResult();
}

```

Answer: D

15. You create an application by using the Microsoft .NET Framework 3.5 and Microsoft ADO.NET. The application connects to a Microsoft SQL Server 2005 database.

You write the following code segment.

```

string query = "Select EmpNo, EmpName from dbo.Table_1;
select Name, Age from dbo.Table_2";
SqlCommand command = new SqlCommand(query, connection);
SqlDataReader reader = command.ExecuteReader();

```

You need to ensure that the application reads all the rows returned by the code segment.

Which code segment should you use?

```

A. while (reader.NextResult())
{
Console.WriteLine(String.Format("{0}, {1}", reader[0], reader[1]));
reader.Read();
}

```

```

B. while (reader.Read())
{
Console.WriteLine(String.Format("{0}, {1}", reader[0], reader[1]));
reader.NextResult();
}

```

```

C. while (reader.Read())
{
Console.WriteLine(String.Format("{0}, {1}", reader[0], reader[1]));
}
reader.NextResult();
while (reader.Read())
{

```

```

Console.WriteLine(String.Format("{0}, {1}", reader[0], reader[1]));
}

```

```

D. while (reader.NextResult())
{
Console.WriteLine(String.Format("{0}, {1}", reader[0], reader[1]));
}

```

```

}
reader.Read();
while (reader.NextResult())
{
Console.WriteLine(String.Format("{0}, {1}",reader[0], reader[1]));
}
Answer: C

```

[More 70-561CSharp Information](#)

Related 70-561CSharp Exams

70-647	<i>Pro: Windows Server 2008,Enterprise Administrator</i>
70-640	<i>TS: Windows Server 2008 Active Directory, Configuring</i>
70-662	<i>TS: Microsoft Exchange Server 2010, Configuring (English)</i>
70-642	<i>TS: Windows Server 2008 Network Infrastructure, Configuring</i>
83-640	<i>TS: Windows Server 2008 Active Directory, Configuring</i>
70-568	<i>Upgrade: Transition your MCPD Enterprise Application Developer Skills to MCPD Enterprise Applications Developer 3.5, Par</i>
70-433	<i>TS: Microsoft SQL Server 2008, Database Development</i>
70-562	<i>TS: MS .NET Framework 3.5, ASP.NET Application Development</i>
70-432	<i>TS:MS SQL Server@ 2008,Implementation and Maintenance</i>
70-660	<i>TS:Windows® Internals</i>
70-643	<i>TS: Windows Server 2008 Applications Infrastructure, Configuring</i>
70-569	<i>Upgrade: Transition your MCPD Enterprise Application Developer Skills to MCPD Enterprise Applications Developer 3.5, Par</i>
70-448	<i>TS:MS SQL Server 2008.Business Intelligence Dev & Maintenan</i>
70-561	<i>TS: MS .NET Framework 3.5, ADO.NET Application Development</i>
70-450	<i>PRO:MS SQL Serv 08,Design,Optimize, & Maintain DB Admin Solu</i>
70-658	<i>TS: System Center Data Protection Manager 2007, Configuring (English)</i>
70-652	<i>TS: Windows Server Virtualization, Configuring</i>
70-563	<i>Pro: Designing and Developing Windows Applications Using the Microsoft .NET Framework 3.5</i>
70-653	<i>TS:Windows Small Business Server 2008, Configuring</i>
70-690	<i>TS: Windows HPC Server 2008, Configuring and Managing (English)</i>

Other Microsoft Exams

111-056	MB7-226	70-272	70-640	MB7-224	70-577	70-660	MB7-638
MB2-633	74-675	70-540VB	70-562VB	MB4-117	70-300	MB3-461	70-443GB2312
70-638	70-658	MB2-298	70-528CSharp				